

**ISO TC 22/SC 12**

Date: 2026-02-18

**ISO/TS 13499 – RED A : 2024(E)**

ISO TC 22/SC 36/WG 3

Secretariat: AFNOR

## **Road vehicles — Multimedia data exchange format for impact tests**

*Véhicules routiers — Format d'échange de données multimédia pour les essais de choc*

### **Related electronic document A**

#### **Examples and Hints**

— Version 1.6 —

Revision 3



## Contents

	Page
A.0 Definition of basic and generic data types.....	2
A.1 Examples of files.....	2
A.1.1 Example of test descriptor file.....	2
A.1.2 Example of test comment file.....	3
A.1.3 Example of channel comment file.....	3
A.1.4 Example of diagram comment file.....	3
A.1.5 Example of movie comment file.....	3
A.1.6 Example of photo comment file.....	4
A.1.7 Example of report comment file.....	4
A.1.8 Example of static comment file.....	4
A.1.9 Example of channel information file.....	4
A.1.10 Example of test channel file.....	4
A.1.11 Examples of moving image information files.....	5
A.1.11.1 Example of moving image information file.....	5
A.1.11.2 Example of image history file.....	6
A.1.11.3 Example of correction parameter file for bundle adjustment.....	6
A.1.12 Example of photo information file.....	7
A.1.13 Example of static data file.....	7
A.2 Hints and changes.....	8
A.2.1 MME file.....	8
A.2.1.1 MME file - Additional descriptors.....	8
A.2.1.2 Barrier information descriptors.....	8
A.2.1.3 Time of the test information.....	8
A.2.2 Test channel files, CHN file and channel comment file.....	9
A.2.2.1 Test channel files - Additional descriptors.....	9
A.2.2.2 Test channel files and CHN file - Hint: Sign convention.....	10
A.2.2.3 Test channel files - Hint: Order of fine locations.....	10
A.2.2.4 Test channel files - Hint: Data from film analysis.....	10
A.2.2.5 Test channel files - Hint: Barrier load cell channel code.....	10
A.2.2.6 Channel comment file - Hint: Channel specific information.....	10
A.2.2.7 Channel file – Additional descriptors for load cells.....	10
A.2.2.8 Test channel files - Hint: Channel numbering.....	10
A.2.2.9 Test channel files – Transducer damping ratio.....	11
A.2.2.10 Test channel files – Transfer function.....	11
A.2.3 MII file.....	12
A.2.3.1 MII file - Correction.....	12
A.2.3.2 MII file - Hint: Single image sequences.....	12
A.2.3.3 MII file - Additional descriptors for 3D film analysis.....	13
A.2.3.4 MII file - Hint for AVI format files.....	13
A.2.3.5 MII file - Additional information about the history of image processing and distortion correction.....	13
A.2.3.5.1 MII file - Additional descriptors for image processing and distortion correction.....	13
A.2.3.5.2 Structure of an image history file.....	13
A.2.3.5.3 Structure of a correction parameter file for bundle adjustment.....	14
A.2.4 PHO file.....	14
A.2.4.1 PHO file - Correction.....	14
A.2.5 Data exchange with the NHTSA.....	14
A.2.6 Calculated value codes and channels.....	14
A.2.7 Channel code – Hint: Naming convention for the position field (Motorcycle).....	15
A.2.8 MME directory structure – Hint: Missing media objects.....	15
A.2.9 Optional descriptors (Dot-Descriptors).....	15
A.2.10 Line length of information files.....	15
A.2.11 Case sensitivity of filenames.....	15
A.2.12 Combination of dummy parts.....	15
A.2.13 MME file - Test object information.....	15
A.2.14 Naming rules for channels.....	16
A.2.15 MME directory structure – Recommendations for special data.....	16

## RED A : Definitions

### A.0 Definition of basic and generic data types

The data types used in the main document and in the chapters below are defined as follows:

Valid basic data types are integer, float. Generic data types are datetime and coded.

alphanumeric: a set of characters according to ISO/IEC 8859-1 without length restrictions.

integer: set of characters representing numbers which don't have any fractional digits.

float: set of characters representing floating-point type with the decimal symbol being a dot (ASCII 46).

datetime: YYYY-MM-DD hh:mm:ss (main document "19 alphanumeric")  
or  
YYYY-MM-DD if time information is unavailable (main document "10 alphanumeric")  
— in accordance with ISO 8601.

coded: enumeration of valid values (see A2.2ff).

## RED A : Examples and Hints

### A.1 Examples of files

#### A.1.1 Example of test descriptor file

**File name :** 2005ISO1.MME

Data format edition number :1.6  
Laboratory name :ALPHA Car Test Laboratory  
Laboratory contact name :Frank N. Stein  
Laboratory contact phone :+49-222/123-4567  
Laboratory contact fax :+49-222/123-8901  
Laboratory contact email :frank.stein@alpha.cartest.com  
Laboratory test ref. number :2005WG3  
Customer name :ISO/TC22/SC12/WG3 Safety Laboratory  
Customer test ref. number :2005IS01  
Customer project ref. number:IS0TC22  
Customer order number :SC12WG3  
Customer cost unit :2001/0  
Customer test engineer name :Mary Land  
Customer test engineer phone:+44-123/555-123  
Customer test engineer fax :+44-123/555-456  
Customer test engineer email:mary.land@iso.tc22.sc12.wg3.uk  
Title :Simulation Test  
Medium no./number of media :1/1  
Timestamp :2005-05-22 14:25:15  
Type of the test :Frontal  
Subtype of the test :40% Offset left 0°  
Regulation :EuroNCAP  
Reference temperature :285.5  
Relative air humidity :75  
Date of the test :2005-05-22  
Number of test objects :2  
Comments :  
Comments : The following block describes test object 1  
Comments :

```

Name of test object 1      :Vehicle A
Velocity test object 1    :15.72
Mass test object 1       :1430.00
Driver position object 1  :1
Impact side test object 1 :FR
Type of test object 1    :1
Class of test object 1   :Small Family Car
Code of test object 1    :A05
Ref. number of test object 1:007-008
.Offset 1                :40
Comments                  :
Comments                  : The following block describes test object 2
Comments                  :
Name of test object 2    :Fixed barrier with load cell matrix
Velocity test object 2   :0.00
Mass test object 2      :NOVALUE
Driver position object 2 :NOVALUE
Impact side test object 2 :FR
Type of test object 2   :B
Class of test object 2  :NOVALUE
Code of test object 2   :NOVALUE
Ref. number of test object 2:NOVALUE
.Barrier width 2        :3.2
.Barrier height 2       :1.64
.Yaw angle 2            :-1.507
.Reference system 2     :laboratory
Comments                 according to the SAE J211 coordinate system
.Origin X 2              :0.12
.Origin Y 2              :-1.4
.Origin Z 2              :-1.8
.Number of loadcells 2   :64

```

### A.1.2 Example of test comment file

**File name :** 2005ISO1.TXT

The **car-to-car** test was performed on 22<sup>nd</sup> of May 2005 at ALPHA Car Test Laboratory.  
The airbags of vehicle A had to be exchanged before the test. ...

### A.1.3 Example of channel comment file

**File name :** CHANNEL.TXT

Following problems occurred:  
11HEAD0000H3ACXA: large deviations at **post-test** calibration ...

### A.1.4 Example of diagram comment file

**File name :** DIAGRAM.TXT

The plots and diagrams of the test are stored as postscript files. ...

### A.1.5 Example of movie comment file

**File name :** MOVIE.TXT

The 16 mm films are scanned with an EPSILON film scanner in 1.020 x 1.360 pixel resolution. The images are resized to 576 x 768 pixel with the program TAU. The creation of the AVI container files was performed with the program AVIMAKER. ...

### A.1.6 Example of photo comment file

File name : PHOTO.TXT

All pictures photographed with the ETA 007 are resized from 5.850 x 5.000 to 1.170 x 1.000 pixel. The resizing and the colour correction are performed with the program TAU. ...

### A.1.7 Example of report comment file

File name : REPORT.TXT

The name of the report file is 2005ISO1\_REPORT.TXT. It contains plain text with up to 80 characters per line and each line is separated by a ,carriage return' and a ,line feed' (CR/LF). ...

### A.1.8 Example of static comment file

File name : STATIC.TXT

The ID-number of the points starts with 7, because the first 6 points define our reference system for frontal impacts. ...

### A.1.9 Example of channel information file

File name : 2005ISO1.CHN

Instrumentation standard	:ISO 6487 (1987) / SAE J211 (MAR95)
Number of channels	:13
Name of channel 001	:11HEAD0000H3ACXA / Head Acceleration X
Name of channel 002	:11HEAD0000H3ACYA / Head Acceleration Y
Name of channel 003	:11HEAD0000H3ACZA / Head Acceleration Z
Name of channel 004	:11CHST0000H3DSXC / Chest Displacement X
Name of channel 005	:14BPILLO0000ACXC / B-Pillar Acceleration X
Name of channel 006	:11NECKUP0000H3FOZA / Neck upper Force Z
Name of channel 007	:11NECKUP0000H3MOYB / Neck upper Moment Y
Name of channel 008	:B0LOMA007525FOXP / Loadcell matrix Force X
Name of channel 009	:B0LOMA007550FOXP / Loadcell matrix Force X
Name of channel 010	:B0LOMA007575FOXP / Loadcell matrix Force X
Name of channel 011	:11TIBILEUPH3FOZB / Tibia left upper Force Z
Name of channel 012	:11TIBILEUPH3MOXB / Tibia left upper Moment X
Name of channel 013	:11TIBILEUPH3MOYB / Tibia left upper Moment Y

**Remark:** In this example you will find a very typical extension to the standard. An additional "longname" is given after the required Channel Code of each channel, divided by a " / " sequence after the Channel Code.

### A.1.10 Example of test channel file

Filename : 2005ISO1.001

Test object number	:1
Name of the channel	:Head Acceleration X
Laboratory channel code	:HEAD01AX
Customer channel code	:1HEAD_X_ACC
Channel code	:11HEAD0000H3ACXA
Comments	: next 4 items are optional and part of the channel code
Location	:Head (= HEAD at code position 3-6)
Dimension	:Acceleration (= AC at code position 13-14)
Direction	:Longitudinal (= X at code position 15)

```

Channel frequency class      :1000          (= A at code position 16)
Unit                        :m/(s*s)
Reference system            :Local
Transducer type             :TAU 7270 A
Transducer id               :42
Pre-filter type             :Butterworth, 6 pole
Cut off frequency          :2000.0
Channel amplitude class     :2000.0
Reference channel           :implicit
Reference channel name      :NOVALUE
Data source                 :transducer
Data status                 :ok
Sampling interval          :0.0001
Bit resolution              :12
Time of first sample        :0.0000
Number of samples          :2500
Offset post test           :0.15
Transducer natural frequency:27000
Transducer damping ratio    :0.5
Comments                    : next 6 items for proofing
First global maximum value  :+1.237802E+02
Time of maximum value      :+0.18450
First global minimum value  : -5.489905E+02
Time of minimum value      :+0.06860
Start offset interval       : -0.0500
End offset interval         :+0.0000
-4.788391E-01
-7.182586E-01
. . .
+3.064578E+01

```

## A.1.11 Examples of moving image information files

### A.1.11.1 Example of moving image information file

**File name :** 2005ISO1.MII

```

Number of movies           :7
Comments                  :
Comments                   : the following block describes movie 1
Comments                   :
ID-number 1               :1
Origin 1                  :Crashtest
Description 1              :total view of vehicle A from the left side
Camera type 1              :KAPPA ROC
Camera ID-number 1         :KAPPA12
Lens ID-number 1          :14579435
Lens type 1                :Schneider
Focus 1                   :infinite
Lens focal length 1        :10
Number of images 1         :350
Film speed 1              :1000
Shutter time 1            :0.0001
Aperture 1                 :5.6 - 8
Time zero 1               :50
Time vector filename 1     :NO
Reference system 1         :middle of the test block, on the floor
Location X 1               : -25.0
Location Y 1               : -9.5
Location Z 1               :1.2

```

Theta X 1 :90  
Theta Y 1 :0  
Theta Z 1 :270  
Width of image 1 :512  
Height of image 1 :384  
Aspect ratio of pixels 1 :1.00  
Colour 1 :RGB  
Name of movie file 1 :LEFTATOT.AVI  
Format of movie file 1 :AVI  
Keyframes 1 : 3  
Codec used 1 :Indeo video 5.11  
Compression 1 :5.1 %  
Distortion index 1 :NOVALUE  
Movie images corrected 1 :NO  
Correction parameter file 1 :KAPPA12\_14579435.COR  
Image history filename 1 :KAPPA12.IMH  
Comments :  
Comments : the following block describes movie 2  
ID-number 2 :2  
.  
.  
.

#### A.1.11.2 Example of image history file

**File name :** see MII file descriptor Image history filename i

Image processing system :SICON V5.2.3  
Image interpolation :SICON V1.2  
Sharpening 1 :5  
Colour matrix 1 :R(113 / 38 / -50), G(-25 / 144 / -19), B(-25 / -50 / 175)  
White balance 1 :175 / 175 / 240  
Brightness 1 :R(15 / 135 / 255), G(15 / 135 / 255), B(15 / 135 / 255)  
Contrast 1 :NOVALUE  
Saturation 1 :1.0  
Hue 1 :NOVALUE  
Gamma 1 :1.5  
Sharpening 2 :8

#### A.1.11.3 Example of correction parameter file for bundle adjustment

**File name :** see MII file descriptor Correction parameter file i

Distortion correction type :bundle adjustment  
Pixel distance x :0.016  
Pixel distance y :0.016  
Principal point x :-9.38  
Principal point y :-8.25  
Calibrated focal length :10.128  
Distortion unit :mm  
Distortion correction A1 :-1.1685e-003  
Distortion correction A2 :5.3873e-006  
Distortion correction A3 :2.8685e-007  
Distortion correction B1 :-1.4558e-005  
Distortion correction B2 :-3.2337e-005  
Distortion correction C1 :6.6139e-007  
Distortion correction C2 :3.6798e-005  
Distortion correction R0 :3.413  
+Method :simple  
+Date of the calibration :2005-03-03

**A.1.12 Example of photo information file****File name : 2005ISO1.PHO**

```

Number of photos      :6
Comments             :
Comments             : the following block describes photo 1
Comments             :
ID-number 1          :1
Test object number   :2
Camera type 1        :ETA 007
Post-test / Pre-test 1 :POST
Description 1        :partial view of the front end of vehicle B
Direction 1          :right
Aperture 1           :8.0
Exposure time 1      :0.008
Comments             : original area of the camera chip 5850 x 5000 pixel
Width of image 1     :1170
Height of image 1    :1000
Aspect ratio of pixels 1 :1.00
Colour 1             :RGB
Name of photo file 1 :BRIGPOST.TIF
Format of photo file 1 :TIFF
Compression 1        :LZW
Comments             :
Comments             : the following block describes photo 2
ID-number 2          :2. . .

```

**A.1.13 Example of static data file****File name : 2005ISO1.SD1**

```

Number of measurements :30
Comments             : the following block describes point 1
Comments             : the first point of the origin
ID-number 1          :7
. . .
Comments             : the following block describes point 7
ID-number 007        :13
Description 007       : Suspension dome right
X Pre 007            :0.017
Y Pre 007            : -0.466
Z Pre 007            :0.545
X Post 007           :0.287
Y Post 007           : -0.398
Z Post 007           :0.589
Comments             : the following block describes point 8
ID-number 008        :14
Description 008       : Sill at B-Pillar. . .

```

## A.2 Hints and changes

### A.2.1 MME file

#### A.2.1.1 MME file - Additional descriptors

To handle the information about the test type more automatically it is meaningful to introduce additional descriptors to specify the subtype of a certain main test type and the regulation for the test. If for example the test type is a "frontal impact" possible values for subtype and regulation could be "ODB" and "Euro NCAP". For every test object (m) the offset value in percent can be described by an optional descriptor.

Additional descriptors for the specification of a test:

Subtype of the test	alphanumeric	
Regulation	alphanumeric	
.Offset m	float	Overlap in percent

Additional descriptors related to the test object velocity (TOB velocity):

Velocity intended TOB x	float	desired velocity for TOB "x"
Velocity lateral TOB x	float	lateral velocity for TOB "x"
Velocity intended lat. TOB x	float	desired lateral velocity for TOB "x"

The following descriptor initially defined for Barrier (see below A.2.1.2) can also be used for other test objects. The yaw angle is then given related to the vehicle longitudinal axis:

.Yaw angle x	float	Angle of test object with respect to direction of travel
--------------	-------	--

#### A.2.1.2 Barrier information descriptors

If the test object m is a barrier, optional descriptors can be used to describe its orientation and loadcell matrix. The coordinate system according to SAE J211/1 MAR95 Instrumentation for Impact Test is described in A.2.2.5

.Barrier width m	float	[m]
.Barrier height m	float	[m]
.Yaw angle m	float	Angle of barrier with normal to direction of vehicle travel. Units: radians. limited to $\pm\pi/2$ . 0 rad means that the barrier is perpendicular to the vehicle. Positive sense: Clockwise when viewed from above (SAE J211)
.Reference system m	alphanumeric	Coordinate reference system e.g., laboratory
.Origin X m	float	[m] Top left corner of the loadcell matrix within the reference system - X coordinate
.Origin Y m	float	[m] Top left corner of the loadcell matrix within the reference system - Y coordinate
.Origin Z m	float	[m] Top left corner of the loadcell matrix within the reference system - Z coordinate
.Number of loadcells m	integer	

#### A.2.1.3 Time of the test information

In some applications the time of the test is needed to identify the sequence of multiple tests. The time information (as local time without time zone) can be added to the 'Date of the test' descriptor. The format should comply to the 'Timestamp' descriptor and the datetime format (see chapter A.0):

Date of the test	:2024-07-08 11:19:04
------------------	----------------------

**A.2.2 Test channel files, CHN file and channel comment file**

**A.2.2.1 Test channel files - Additional descriptors**

Additional descriptors for time channel reference:

Reference channel	coded possible values: <b>implicit</b> Time reference is given with the descriptor values 'Time of first sample' and 'Sampling interval' <b>explicit</b> Explicit time channel exists in test data. Channel name is given with the descriptor 'Reference channel name' <b>NOVALUE</b> No time reference is available. For example, in case of constant channels (filter class 'X').
Reference channel name	Name of reference channel in test data if reference channel value 'explicit' is used. Then provide a code based on the mask ??TIRS?????TI?0 otherwise NOVALUE

Additional descriptor for channel data source and status:

Data source	coded possible values: <b>transducer</b> Channel data has been generated by transducer <b>calculation</b> Channel data has been calculated from other channels <b>camera</b> Channel data has been generated by film analysis <b>simulation</b> Channel data has been generated by simulation <b>parameter</b> Channel data can be constant or limit curve
-------------	--

New categories for Data status (2024-08):

The Data status property has been reviewed and redefined to allow a distinct decision of the validity of the data for the analysis/processing/assessment. The new categories are:

Data status coded

Status Possible Values	Explanation	Data modified	Valid for Analysis
ok	faultless sample data	no	yes
partially failed	failure is outside the important time range	no	yes
corrected data	data have been corrected (e.g., by multiplying by a certain factor ("scaling factor applied", also inverting) or by interpolating parts of the channel ("linearised data") so that they can be used for assessment; excluding: renaming, offset correction	yes	yes
questionable data	needs to be validated	no	no
no data	no sample data available or NOVALUES only	no	no
channel failed	channel failed completely or in the important time range, if caused e.g. by the sensor or sensor cable	no/yes	no
system failed	channel failed completely or in the important time range, if caused e.g. by the data recorder	no/yes	no
NOVALUE	no status information available (e.g. in case of raw data)	?	no/yes

Table 1: Data Status values and applicability

Equivalent values	
Old Status (1.6.2)	New Status (1.6.3+)
scaling factor applied	use "corrected data"
linearised data	use "corrected data"
meaningless data	use "partially failed"



Channels with a number up to 999 will keep their 3-digit file extension. Channels with a higher number will use as much digits as needed:

```
<testname>.001
<testname>.002
...
<testname>.999
<testname>.1000
<testname>.1001
...
```

**A.2.2.9 Test channel files – Transducer damping ratio**

For the description of the overall frequency response of a transducer channel and the entire data collection system two new mandatory descriptors are necessary.

```
Transducer natural frequency float [Hz]
Transducer damping ratio float [1]
```

**A.2.2.10 Test channel files – Transfer function**

For a long time, only linear regression has been used to describe the calculation of physical units from the transducer signal. New types of transducers and new regulations require an extended concept of the describing parameters. The way from the transducer signals to the exchanged data can be described as a set of transfer functions.

Use case	Application	Transfer function
Linear transducer with relative measurement	Standard for most transducers	Linear regression
Linear transducer with absolute measurement	Absolute pressure, angle transducer in <b>MTRACs</b>	Linear regression with offset
Nonlinear transducer with polynomial approximation	Polynomial calibrated belt force	Polynomial regression 3rd order
Nonlinear transducer with power function approximation	Displacement transducer in the <b>IR-TRACC</b>	Power function
Linear transducer with relative measurement and additional polynomial calibration <sup>1)</sup>	Chest deflection of H III Dummy	Linear regression

**Tab 1:** Use cases for transfer functions

<sup>1)</sup> In the case of chest deflection measurement, the data has to be calculated and exchanged with the *Linear regression* transfer function. In the channel file header, the used parameters and in addition the parameters necessary for the calculation of the *Polynomial regression 3rd order* transfer function have to be stored. This functionality needs different descriptors for both transfer functions.

For all use cases described in **Tab 1** a specific set of descriptors are defined in **Tab 2**. The descriptors of the transfer functions are in principle optional, but if a specific function is named in the channel header, the set of associated descriptors has to be complete.

Transfer function	Formula		Descriptor	Unit
Necessary for all functions	D : physical value [Unit] S : sensor output reading [eU]		.Transfer function used .Direction polarity Offset post test	- - [Unit]
Linear regression	$D = C * S$	C	Inverse sensitivity Offset pre test .Sensitivity <sup>2)</sup>	[Unit/eU] [eU] [eU/Unit]
Linear regression with offset	$D = C * S + M$	C M	Inverse polynom coeff C Inverse polynom coeff M	[Unit/eU] [Unit]

			Offset pre test	[eU]
Polynomial regression 3rd order	$D = A * S^3 + B * S^2 + C * S + M$	A	Inverse polynom coeff A	[Unit/(eU) <sup>3</sup> ]
		B	Inverse polynom coeff B	[Unit/(eU) <sup>2</sup> ]
		C	Inverse polynom coeff C	[Unit/eU]
		M	Inverse polynom coeff M	[Unit]
Power function	$D = C * (S + S_0)^{\alpha} + M$	C	.Power func sensitivity	[Unit/eU]
		M	.Power func eng offset	[Unit]
		S <sub>0</sub>	.Power func electr offset	[eU]
		α	.Power func exponent	[1]

Tab 2: Parameters and descriptors of transfer functions

2) Additional information: must not be used if ~~Inverse sensitivity is missing or NOVALUE~~ **old**  
 must not be used if **Inverse sensitivity is available and not NOVALUE** **new**

The function *Linear regression with offset* is a special case of *Polynomial regression with offset* where the cubic and quadratic coefficients are 0.  
 Independent from the transfer function the descriptor ‘*Offset post test*’ can be used to document the offset correction in physical units in the time between ‘*Start offset interval*’ and ‘*End offset interval*’.

### A.2.3 MII file

#### A.2.3.1 MII file - Correction

The data format for the descriptor ‘*Aperture i*’ was specified as a float value. In practice it is often necessary to store an intermediate value like “5.6 – 8”. Therefore, the new data format specification is alphanumeric.

#### A.2.3.2 MII file - Hint: Single image sequences

In most cases of movie exchange container files like AVI are used. Especially for film analysis it could be necessary to exchange the original single images. To avoid equivocal filenames the best method is to store every sequence of single images within an own subdirectory of the movie directory. The name of the subdirectory shall be equal to the container filename without extension. The names of the single image files shall contain numbers for sorting. The descriptive parameters of the container file and the image sequence are partly different. Therefore, it is necessary to use two distinct information blocks within the MII file if both are exchanged. For the whole image sequence only one descriptor ‘*Name of moviefile i*’ can be used. It shall contain only the subdirectory name without dots and pathnames.

Example for the image sequence F00000.IMG ... F00299.IMG in the subdirectory LEFT1 together with the container file LEFT1.AVI:

```

...
Number of images 1           :200
Time zero 1                  :5
Width of image 1             :512
Height of image 1            :512
Colour 1                      :RGB
Name of movie file 1         :LEFT1.AVI
Format of movie file 1       :AVI
Codec used 1                  :Indeo video 5.11
Compression 1                 :5 %
...
Number of images 2           :300
Time zero 2                   :10
Width of image 2             :1024
Height of image 2            :1024
Colour 2                      :RGB
Name of movie file 2         :LEFT1
Format of movie file 2       :TIFF
    
```

Codec used 2	uncompressed
Compression 2	NOVALUE
...	

All other descriptive data should be equal for both kinds of movie.

### A.2.3.3 MII file - Additional descriptors for 3D film analysis

Camera ID-number i	alphanumeric
Lens ID-number i	alphanumeric
Lens type i	alphanumeric
Focus i	alphanumeric

### A.2.3.4 MII file - Hint for AVI format files

The recommended compression algorithm for the use in AVI files is **X264** Revision 1195. This codec may be used with the following parameters:

#### Single pass – ratefactor-based (CRF)

Ratefactor	23 or less
FourCC	X264
ME algorithm	umh
Subpixel ME refinement	7 RD on all
Min. GOP Size	7
Max. GOP Size	7
Max. Number of consecutive B-Frames	0

The first frame of an AVI file has the number 0. It has to be considered for the calculation of the “Time zero” value.

### A.2.3.5 MII file - Additional information about the history of image processing and distortion correction

#### A.2.3.5.1 MII file - Additional descriptors for image processing and distortion correction

The history of the image processing and also the parameters for the distortion correction may be stored in special files in the movie subdirectory referenced by:

Image history filename i	alphanumeric	according to the filename convention
Correction parameter file i	alphanumeric	according to the filename convention

Additional information about the distortion correction and the quality of the optical chain shall be given by:

Distortion index i	float	[%] Distortion index according to ISO 8721
Movie images corrected i	alphanumeric	<b>YES</b> or <b>NO</b> are the images corrected with the distortion parameters?

#### A.2.3.5.2 Structure of an image history file

The image history file is optional. The descriptors are not mandatory. They are unique but their position order shall show the time history of the single processing steps. The numbering of the descriptors is used to decide between twice or more usage of the same processing item.

Image processing system	alphanumeric	with version number
Image interpolation	alphanumeric	with version number

Sharpening i	alphanumeric	typically 1 integer value
Colour matrix i	alphanumeric	
White balance i	alphanumeric	typically 3 integer values
Brightness i	alphanumeric	single or matrix of integer
Contrast i	alphanumeric	single or matrix of integer
Saturation i	alphanumeric	integer or float
Hue i	alphanumeric	typically integer
Gamma i	alphanumeric	typically 1 float value

**A.2.3.5.3 Structure of a correction parameter file for bundle adjustment**

The correction parameter file is optional. The file content for the correction method *bundle adjustment* shall be:

Distortion correction type	alphanumeric	<b>bundle adjustment</b>
Pixel distance x	float	[mm]
Pixel distance y	float	[mm]
Principal point x	float	[pixel] deviation from the <b>center</b> of the image (positive from left to right)
Principal point y	float	[pixel] deviation from the <b>center</b> of the image (positive from top to bottom)
Calibrated focal length	float	[mm] as positive value
Distortion unit	alphanumeric	<b>pixel</b> or <b>mm</b> unit for all following distortion parameters
Distortion correction A1	float	1. corr. coeff. for radial symmetrical distortion
Distortion correction A2	float	2. corr. coeff. for radial symmetrical distortion
Distortion correction A3	float	3. corr. coeff. for radial symmetrical distortion
Distortion correction B1	float	1. corr. coeff. for radial asymmetrical distortion
Distortion correction B2	float	2. corr. coeff. for radial asymmetrical distortion
Distortion correction C1	float	affinity
Distortion correction C2	float	non-orthogonality
Distortion correction R0	float	2. zero crossing of the distortion curve

Additional descriptors shall start with a '+' sign. **(Do we have this in a prominent general statement? See A.2.9)**  
 The descriptors for other correction methods shall be agreed between the partners.

**A.2.4 PHO file**

**A.2.4.1 PHO file - Correction**

The data format for the descriptor '*Aperture i*' was specified as a float value. In practice it is often necessary to store an intermediate value like "5.6 – 8". Therefore, the new data format specification is alphanumeric. The allowed values for the descriptor '*Post-test / Pre-test i*' are changed to POST, PRE, DURING, NOVALUE.

**A.2.5 Data exchange with the NHTSA**

The additional information for data exchange with the NHTSA shall be placed in special files in the subdirectory NHTSA. For detailed specification see RED D Version 1.6 .

**A.2.6 Calculated value codes and channels**

It is possible now to exchange calculated value codes and channels. For detailed specification see RED E

Version 1.6 .

### **A.2.7 Channel code – Hint: Naming convention for the position field (Multi row, Motorcycle)**

For special seat arrangements with different rows or more than three seats per row the usage of capital letters A - Z for the position field is recommended.

The old code value “D” for Motorcycle Driver is now changed into “2”, the old code value “S” for Motorcycle Sozius/**Pillion rider** is changed into “5”.

### **A.2.8 MME directory structure – Hint: Missing media objects**

Subdirectories and their information files for missing media objects are no longer mandatory.

### **A.2.9 Optional descriptors (Dot-Descriptors)**

Optional descriptors can be introduced in all ISO-MME information files. They have to begin with a “.”.

### **A.2.10 Line length of information files**

The lines of all information files can exceed 80 characters if agreed between the transferring parties.

### **A.2.11 Case sensitivity of filenames**

Parts of filenames and extensions like the testnumber, which occur several times in the file structure, have to be identical in the usage of upper- and lower-case letters.

### **A.2.12 Combination of dummy parts**

When combining parts of different dummy types, a unique FineLocation3 has to be used. Especially when using THOR legs together with the 50<sup>th</sup> percentile male Hybrid III the FineLocation3 should be **T3** for all dummy channels.

### **A.2.13 MME file - Test object information**

For the descriptor ‘*Class of test object m*’ the EuroNCAP class or the platform type is recommended for vehicles. The descriptor ‘*Code of test object m*’ should refer to the code of model type or stage of development for vehicles and to the code of Fine Location 3 for pedestrian impactors. The ‘*Ref. number of test object m*’ should be a unique identification number like the vehicle Id.

#### A.2.14 Naming rules for channels

For the Channel Codes the following general naming rules apply:

- The **MainLocation** should describe the position of the measurement point.
- **ChannelCodes** which deviate from the following rules but are in use for a long time should not be changed.

Especially for new dummy and impactor channels the following naming rules apply:

- The naming of the channels should describe the structure of the dummy as a measurement device.
- The **FineLocation1** should describe the most significant spatial orientation of the channel.
- The **FineLocation2** should describe the less significant characteristic of the channel location or property.
- The **FineLocation3** is identical to the dummy code.

In addition, for all other channels where the **FineLocation3** is not reserved for the dummy code the following rules apply:

- The **FineLocation 1,2,3** should be used in the order X,Y,Z in the coordinate system of the testobject, if all three spatial directions are used.
- If one or two spatial directions are unused the other move up, resulting in 00 values at the **FineLocations 3** and possibly **2**.

#### A.2.15 MME directory structure – Recommendations for special data

For the exchange of data files with CAN-Bus or FlexRay protocols the subdirectory **Busdata** should be used.

For the exchange of simulation input- or output-decks the subdirectory **Simulation** should be used.

The additional data according ISO TS 23520 'Equipment eXchange – data format specification for operational information relevant for equipment exchange and testing' should be exchanged in the subdirectory **Equipment**.