

Road vehicles — Multimedia data exchange format for impact tests

Véhicules routiers — Format d'échange de données multimédia pour les essais de choc

Related electronic document A

Descriptors and Hints

Version 2.0 Draft 20111212

Meaning of the colour marks:

black	no change to the old version 1.5/1.6
red	proposed change or addition to version 1.5/1.6
yellow backgr	changes in the draft

Contents

	Page
1	Data formats 3
1.1	Physical units 3
1.2	Definition of basic and generic data types 3
1.3	Information files 3
1.3.1	General rules 3
1.3.2	Test information 3
1.3.2.1	Additional NHTSA test information 5
1.3.2.2	Additional biomechanical test information 5
1.3.3	Object information 6
1.3.3.1	Standard testobject information 6
1.3.3.2	Additional NHTSA testobject information 7
1.3.3.3	Additional biomechanical testobject information 8
1.3.3.4	Occupant information 8
1.3.3.5	Restraint system information 10
1.3.4	Reference system information 10
1.3.5	Channel information 11
1.3.6	Moving image information 11
1.3.6.1	Moving image information file 11
1.3.6.2	Correction parameter file 12
1.3.6.3	Image history file 13
1.3.7	Photo information 14
1.3.8	Additional information files 14
1.4	Data files 15
1.4.1	General rules 15
1.4.2	Channel data files 15
1.4.3	Multi column data files 17
1.4.4	Static measurement data file 17
1.4.5	Reference system data file, Camera position file and Object data file 18
1.4.6	3D point data file 20
1.5	Comment files 21
2	Coded values 22
2.1	Valid values for the descriptor 'Data format edition number' 22
2.2	Valid values for the descriptor 'Data structure' 22
2.3	Valid values for the descriptor 'Reference system id' 22
2.4	Valid values for the descriptor 'Data source' 22
2.5	Valid values for the descriptor 'Data status' 23
2.6	Valid values for the descriptor 'Reference channel' 23
2.7	Valid values for the descriptor 'Classification' 23
2.8	Valid values for the descriptor 'Movie images corrected' 23
2.9	Valid values for the descriptor 'Distortion correction type' 23
2.10	Valid values for the descriptor 'Distortion unit' 24
2.11	Valid values for the descriptor 'Gender' 24
2.12	Valid values for the descriptor 'Time zone' 24
2.13	Valid values for block descriptors 24
2.14	Valid values for the format specification 24
2.15	Valid values for the data origin 25
2.16	Valid values for the codeextension 25
2.17	Allowed units 25
2.18	Valid values for the descriptor 'Type of the test' 27
2.19	Valid values for the descriptor 'Regulation' 27
3	Hints 28
4	Examples 29
4.1	Examples of information files 29
4.1.1	Examples of test information files 29
4.1.1.1	Example of MME file 29
4.1.1.2	Example of additional NHTSA test information 29
4.1.1.3	Example of additional biomechanical test information 30

4.1.2	Examples of object information files	30
4.1.2.1	Example of vehicle information file	30
4.1.2.2	Example of barrier information file	30
4.1.2.3	Example of occupant information file	31
4.1.2.4	Example of restraint system information file.....	31
4.1.3	Example of reference system information file.....	32
4.1.4	Example of channel information file	32
4.1.5	Examples of moving image information	33
4.1.5.1	Example of moving image information file	33
4.1.5.2	Example of COR file	34
4.1.6	Example of photo information file.....	34
4.1.7	Example of report information file	34
4.2	Examples of data files	35
4.2.1	Example of multi column data file.....	35
4.2.2	Example of reference system data file	35
4.2.3	Examples of channel data.....	36
4.2.3.1	Example of channel data file with local transducer data.....	36
4.2.3.2	Example of channel data file with filmanalysis data	37
4.2.4	Example of static measurement data file	37
4.2.5	Example of 3D point data file.....	37
4.2.6	Example of camera position file.....	37
4.3	Example of comment files	38
4.3.1	Example of test comment file	38
4.3.2	Example of channel comment file.....	38

1 Data formats

1.1 Physical units

Data and descriptor values have to be expressed in SI units. Table 2.17 shows the allowed physical units in their notation. If decimal submultiples or agreed units deviant from the defaults described in this document are used, the numerical value has to be followed by the unit enclosed in squared brackets.

1.2 Definition of basic and generic data types

Valid basic data types are integer, float and string. Generic data types are date, datetime, coded, reference and filereference.

string:	a set of characters according to ISO/IEC 8859-1 without length restrictions.
integer:	set of characters representing numbers which don't have any fractional digits.
float:	set of characters representing floating-point type with the decimal symbol being a dot (ASCII 46).
date:	YYYY-MM-DD — in accordance with ISO 8601.
datetime:	YYYY-MM-DD hh:mm:ss — in accordance with ISO 8601.
coded:	enumeration of valid values (see 2 Coded values).
reference:	value of a channel code part or id used within another file. References are built from the lexical space ASCII {48 – 57, 65 – 90, 95, 97 – 122}.
filereference:	filename with extension but without path information (according to the filename convention).

1.3 Information files

1.3.1 General rules

The following rules specify the general handling of information files (see main document 5.1).

Mandatory and optional descriptors are built from the lexical space ASCII {48 – 57, 65 – 90, 97 – 122}. Additional descriptors agreed between the transferring parties have to start with a "+" sign (ASCII 43).

The information of <mediatype> like channel, photo, movie and also <testobject> is described in a block structure. Every block starts with a blockbegin-descriptor and ends with a blockend-descriptor. Within a block the position order of the information lines is free.

The hash-symbol "#" (ASCII 35) is restricted to the blockbegin- and blockend-descriptors. These descriptors don't have a value.

All descriptors belonging to the collectivity of media objects of the same type have to be positioned before the first block.

Blocking within a block is not allowed. Valid block-descriptors have to be defined in this document or agreed between the exchanging partners.

1.3.2 Test information

The information about the test has to be stored in the test information file in the main directory. The file extension is "mme". In addition to the standard descriptors special blocks for the NHTSA and for biomechanical testinformations are described.

MME standard file

Table 1 — Test information (MME) file

File name:	“filename”.mme, where “filename” is identical to the <testnumber>.			
Location:	main directory			
Contents (for example see 4.1.1.1)				
Descriptor	Mand.	Unit	Data type	Remark
Data format edition number	YES		coded	2.0draft (see 2.1)
Timestamp	YES		datetime	creation date of this medium.
Time zone	YES		coded	see 2.12
Laboratory name	YES		string	
Laboratory contact name	YES		string	person to contact
Laboratory contact phone	YES		string	
Laboratory contact fax	YES		string	
Laboratory contact email	YES		string	
Laboratory test ref number	YES		string	
Customer name	NO		string	
Customer test ref number	NO		string	
Customer project ref number	NO		string	
Customer order number	NO		string	
Customer cost unit	NO		string	
Customer contact name	NO		string	
Customer contact phone	NO		string	
Customer contact fax	NO		string	
Customer contact email	NO		string	
Title	NO		string	
Comments	NO		string	
Type of the test	YES		string	see 2.18
Subtype of the test	YES		string	
Regulation	YES		string	see 2.19
Date of the test	YES		date	
Reference temperature	NO	K	float	measurement point depends on type of the test.
Relative air humidity	NO	%	float	measurement point depends on type of the test.
Number of testobjects	YES		integer	NOVALUE is not allowed
If 'Number of testobjects' > 0				
#Begin of testobject	YES			
Type	YES		reference	see "Test Object" Column 1 in related electronic document <i>Channel Codes</i> .
Filename	YES		filereference	name of the testobject information file (see 1.3.3)
#End of testobject	YES			

1.3.2.1 Additional NHTSA test information

Additional information concerning the test set up and/or conditions required making the ISO-MME impact test dataset transportable into the NHTSA EV5 data exchange format has to be added to the test information file within an own optional information block.

Refer to the NHTSA Test Reference Guide, Volume 1, Vehicle Tests, General Test information section, Version 5 (NTRGV1.PDF -- referred to as **NHTSA -TRG** in the “Remarks” column) for extended field definitions and codes. This document is available on the NHTSA web site at

<http://www-nrd.nhtsa.dot.gov/software/test-reference-guides/test-reference-guides.html>

File name:	“filename”.mme, where “filename” is identical to the <testnumber>.			
Location:	main directory			
Contents (for example see 4.1.1.2)				
Descriptor	Mand.	Unit	Data type	Remark
#Begin of NHTSA				
Test configuration	YES		coded	see NHTSA -TRG
Closing speed	YES	m/s	float	see NHTSA -TRG
Impact angle	YES	rad	integer	using [°] see 2.17
Side impact point	YES	m	float	see NHTSA -TRG
Test type	NO		coded	see NHTSA -TRG
Track surface	NO		coded	see NHTSA -TRG
Track condition	NO		coded	see NHTSA -TRG
NHTSA Offset	NO	m	float	see NHTSA -TRG
NHTSA Comments	NO		string	multiple lines, 70 char maximum
#End of NHTSA				

1.3.2.2 Additional biomechanical test information

Additional biomechanical information concerning the test set up has to be added to the test information file within an own optional information block.

File name:	“filename”.mme, where “filename” is identical to the <testnumber>.			
Location:	main directory			
Contents (for example see 4.1.1.3)				
Descriptor	Mand.	Unit	Data type	Remark
#Begin of biomechanical				
Financial support	YES		string	for instance EC or national program
Project ref number	YES		string	for instance Contract number of the EC project
Project contact name	YES		string	name of the coordinator of the project
Project contact email	YES		string	
#End of biomechanical				

1.3.3 Object information

All information concerning testobjects, occupants and restraint systems has to be stored in the Object-subdirectory. Allowed filenames are built from the testnumber and the first characters of the channel codes: the testobject, the position and the main location. Every object is described in an own file with the file extension “mmi”.

For testobjects the filenames consist of the <testnumber> and the <testobject>. For occupants the filenames consist of the <testnumber>, <testobject> and <position>. For restraint systems the filenames consist of the <testnumber>, <testobject>, <position> and <mainlocation> with AIRB and SEBE stored in separate files.

The MME file contains only the information about the number and the type of testobjects and the testobject information filenames.

1.3.3.1 Standard testobject information

File name:	“filename”.mmi, where “filename” is identical to the <testnumber>_<testobject>.			
Location:	Object-subdirectory			
Contents for all testobject types (for example see 4.1.2)				
Descriptor	Mand.	Unit	Data type	Remark
Name	YES		string	
Velocity	YES	m/s	float	at time zero
Mass	YES	kg	float	
Impact side	YES		coded	see “Fine Location 1” in related electronic document <i>Channel Codes</i> .
Driver position	NO		coded	see “Position” in related electronic document <i>Channel Codes</i> .
Class	NO		string	
Code	NO		string	
Ref number	NO		string	
Offset	NO	%	float	overlap in percent
Additional contents for testobject types B and M				
Barrier width	NO	m	float	mandatory for testobject B and M
Barrier height	NO	m	float	mandatory for testobject B and M
Yaw angle	NO	rad	float	mandatory for testobject B and M Angle of barrier with normal to direction of vehicle travel. Units: radians limited to $\pm\pi/2$. 0 rad means that the barrier is perpendicular to the vehicle. Positive sense: Clockwise when viewed from above (SAE J211)
Reference system id	NO		reference	mandatory if a loadcell matrix is used coordinate reference system for the loadcell matrix (see 1.3.4)
Origin X	NO	m	float	mandatory if a loadcell matrix is used top left corner of the loadcell matrix within the reference system – X coordinate
Origin Y	NO	m	float	mandatory if a loadcell matrix is used top left corner of the loadcell matrix within the reference system – Y coordinate

Origin Z	NO	m	float	mandatory if a loadcell matrix is used top left corner of the loadcell matrix within the reference system – Z coordinate
Number of loadcells	NO		integer	mandatory if a loadcell matrix is used

1.3.3.2 Additional NHTSA testobject information

Additional information concerning the testobjects required making the ISO-MME impact test dataset transportable into the NHTSA EV5 data exchange format has to be added to the testobject information files (see 1.3.3.1) within an own optional information block.

Refer to the NHTSA Test Reference Guide, Volume 1, Vehicle Tests, General Test information section, Version 5 (NTRGV1.PDF -- referred to as **NHTSA -TRG** in the “Remarks” column) for extended field definitions and codes. This document is available on the NHTSA web site at

<http://www-nrd.nhtsa.dot.gov/software/test-reference-guides/test-reference-guides.html>

File name:	“filename”.mmi, where “filename” is identical to the <testnumber>_<testobject>.			
Location:	Object-subdirectory			
Contents for testobject vehicle (for example see 4.1.2.1)				
Field descriptor	Mand.	Unit	Data type	Remark
#Begin of NHTSA				
Vehicle make	YES		string	free text
Vehicle model	YES		string	free text
Vehicle year	YES		integer	4 digit year
Body type	YES		coded	see NHTSA -TRG
VIN	YES		string	free text
Vehicle test weight	YES	kg	integer	see NHTSA -TRG
Wheel base	YES	m	float	see NHTSA -TRG
Vehicle length	YES	m	float	see NHTSA -TRG
Vehicle width	YES	m	float	see NHTSA -TRG
Vehicle center of gravity	YES	m	float	see NHTSA -TRG
Vehicle speed	YES	m/s	float	see NHTSA -TRG
Crab angle	YES	rad	float	using [°] see 2.17
Angle of moving cart	YES	rad	float	using [°] see 2.17
Veh orientation on cart	YES	rad	float	using [°] see 2.17
Engine type	NO		coded	see NHTSA -TRG
Engine size	NO	L	float	
Transmission type	NO		coded	see NHTSA -TRG
Steering column separation	NO		coded	see NHTSA -TRG
Column collapse mechanism	NO		coded	see NHTSA -TRG
Vehicle modifications	NO		string	50 characters maximum
Principal dir of force	NO	rad	float	using [°] see 2.17
Bumper engagement	NO		coded	see NHTSA -TRG
Sill angagement	NO		coded	see NHTSA -TRG

A-Pillar engagement	NO		coded	see NHTSA -TRG
Damage profile distance 1	NO	m	float	see NHTSA -TRG
Damage profile distance 2	NO	m	float	see NHTSA -TRG
Damage profile distance 3	NO	m	float	see NHTSA -TRG
Damage profile distance 4	NO	m	float	see NHTSA -TRG
Damage profile distance 5	NO	m	float	see NHTSA -TRG
Damage profile distance 6	NO	m	float	see NHTSA -TRG
Vehicle damage index	NO		coded	see NHTSA -TRG
Total length indentation	NO	m	float	see NHTSA -TRG
Center damaged area to CG	NO	m	float	see NHTSA -TRG
Maximum crush distance	NO	m	float	see NHTSA -TRG
#End of NHTSA				
Contents for testobject barrier (for example see 4.1.2.2)				
Descriptor	Mand.	Unit	Data type	Remark
#Begin of NHTSA				
Barrier shape	NO		coded	see NHTSA -TRG
Rigid or deformable barrier	NO		coded	see NHTSA -TRG
Angle of fixed barrier	NO	rad	float	using [°] see 2.17
Diameter of pole barrier	NO	m	float	see NHTSA -TRG
NHTSA Comments	NO		string	Multiple lines, 70 char maximum
#End of NHTSA				

1.3.3.3 Additional biomechanical testobject information

Additional biomechanical information concerning the testobjects has to be added to the testobject information files. Biomechanical tests are mostly performed with a test subject on a test device. The test device has to be described as one of the possible testobjects (see Column 1 in related electronic document *Channel Codes*). The test subject has to be described within an occupant information file (see 1.3.3.4)

File name:	"filename".mmi, where "filename" is identical to the <testnumber>_<testobject>.			
Location:	Object-subdirectory			
Contents				
Descriptor	Mand.	Unit	Data type	Remark
Acceleration	NO	m/(s*s)	float	maximum of acceleration

1.3.3.4 Occupant information

The occupant information for all dummies, volunteers or PMHS have to be stored within separate files in the Object-subdirectory.

Refer to the NHTSA Test Reference Guide, Volume 1, Vehicle Tests, General Test information section, Version 5 (NTRGV1.PDF -- referred to as **NHTSA -TRG** in the "Remarks" column) for extended field definitions and codes. This document is available on the NHTSA web site at

<http://www-nrd.nhtsa.dot.gov/software/test-reference-guides/test-reference-guides.html>

File name:	“filename”.mmi, where “filename” is identical to the <testnumber>_<testobject><position>.			
Location:	Object-subdirectory			
Contents (for example see 4.1.2.3)				
Descriptor	Mandatory	Unit	Data type	Remark
Gender	NO		coded	mandatory for biomechanical tests see 2.11
Age	NO		float	mandatory for biomechanical tests in years
Dummy type	NO		coded	mandatory for NHTSA tests see “Fine Location 3” in related electronic document <i>Channel Codes</i> .
Dummy subtype	NO		string	e.g. Build Level D
Dummy id	NO		string	
Dummy manufacturer Ser No	NO		string	50 characters maximum
Dummy modifications	NO		string	50 characters maximum
Dummy temperature	NO	K	float	
Out of position	NO		coded	YES or NO
Head to windshield header	NO	m	float	see NHTSA -TRG
Head to windshield	NO	m	float	see NHTSA -TRG
Head to side header	NO	m	float	see NHTSA -TRG
Head to side window	NO	m	float	see NHTSA -TRG
Chest to dash	NO	m	float	see NHTSA -TRG
Chest to steering wheel	NO	m	float	see NHTSA -TRG
Arm to door	NO	m	float	see NHTSA -TRG
Hip to door	NO	m	float	see NHTSA -TRG
Knees to dash	NO	m	float	see NHTSA -TRG
Head to seatback	NO	m	float	see NHTSA -TRG
Neck to seatback	NO	m	float	see NHTSA -TRG
Chest to seatback	NO	m	float	see NHTSA -TRG
Knee to seatback	NO	m	float	see NHTSA -TRG
Seat track position	NO		coded	mandatory for NHTSA tests see NHTSA -TRG
1st contact for head	NO		coded	see NHTSA -TRG
2nd contact for head	NO		coded	see NHTSA -TRG
1st contact for chest abdo	NO		coded	see NHTSA -TRG
2nd contact for chest abdo	NO		coded	see NHTSA -TRG
1st contact for legs	NO		coded	see NHTSA -TRG
2nd contact for legs	NO		coded	see NHTSA -TRG
Head injury criterion HIC	NO	1	integer	nondimensional
Lo HIC time interval	NO	s	float	
Up HIC time interval	NO	s	float	
Thorax peak accel (CLIP3M)	NO	m/(s*s)	float	

L femur peak load	NO	N	float	
R femur peak load	NO	N	float	
Chest severity index	NO	1	integer	nondimensional
Lap belt peak load	NO	N	integer	
Shoulder belt peak load	NO	N	integer	
Thoracic trauma index	NO	1	float	nondimensional
Pelvis acceleration	NO	m/(s*s)	float	
NHTSA Comments	NO		string	multiple lines, for NHTSA 70 char max.

1.3.3.5 Restraint system information

Additional information concerning airbags and seatbelts has to be added to the restraint system information files in the Object-subdirectory.

File name:	“filename”.mmi, where “filename” is identical to the <testnumber>_<testobject><position><main location>.		
Location:	Object-subdirectory		
Contents (for example see 4.1.2.4)			
Descriptor	Mandatory	Data type	Remark
Restraint type	YES	coded	see NHTSA -TRG
Restraint mount	NO	coded	see NHTSA -TRG
Restraint deployed	NO	coded	see NHTSA -TRG
NHTSA Comments	NO	string	multiple lines, for NHTSA 70 char max.

1.3.4 Reference system information

The descriptive information about all reference systems has to be stored within one reference system information file in the Object-subdirectory.

File name:	“filename”.mmi, where “filename” is identical to the <testnumber>_Reference.		
Location:	Object-subdirectory		
Contents (for example see 4.1.3)			
Descriptor	Mandatory	Data type	Remark
Number of references	YES	integer	NOVALUE is not allowed
... descriptors, which are valid for all references			
For each reference, if ‘Number of references’ > 0			
#Begin of reference			
Reference system id	YES	coded	Id used in the reference system data file (see 2.3)
Description	NO	string	general description of the reference coordinate system
X origin	NO	string	description of the origin – X component
Y origin	NO	string	description of the origin – Y component

Z origin	NO	string	description of the origin – Z component
X direction	NO	string	description of the longitudinal axis orientation
Y direction	NO	string	description of the transversal axis orientation
Z direction	NO	string	description of the vertical axis orientation
Comments	NO	string	
#End of reference			

1.3.5 Channel information

The descriptive information about all channels has to be stored in the header section of each channel file. The main use of the channel information file is for sorting.

File name:	"filename".mmi, where "filename" is identical to the <testnumber>_Channel.		
Location:	Channel-subdirectory		
Contents (for example see 4.1.4)			
Descriptor	Mand.	Data type	Remark
Number of channels	YES	integer	NOVALUE is not allowed
... descriptors, which are valid for all channels			
For each channel, if 'Number of channels' > 0			
#Begin of channel			
Channel code	YES	coded	see "Channel code" in related electronic document <i>Channel Codes</i> .
Reference system id	NO	coded	Id used in the reference system data file (see 2.3)
Data origin	NO	coded	Id used in the reference system data file (see 2.15)
All descriptors which are specified within the channel file headers (see 1.4.2) are possible but optional. The information of the channel file overrides the information of this file.			
#End of channel			

1.3.6 Moving image information

1.3.6.1 Moving image information file

The descriptive information about all films, videos and image sequences has to be stored within one moving image information file in the Movie-subdirectory. If a single image sequence is referenced, the value for 'Name of the movie file' has to point to a subdirectory of the MOVIE directory.

File name:	"filename".mmi, where "filename" is identical to <testnumber>_Movie.			
Location:	Movie-subdirectory			
Contents (for example see 4.1.5.1)				
Descriptor	Mand.	Unit	Data type	Remark
Number of movies	YES		integer	NOVALUE is not allowed

... descriptors, which are valid for all movies				
For each movie, if 'Number of movies' > 0				
#Begin of movie				
Movie id	YES		reference	Id of the movie for referencing
Name of movie file	YES		filereference	
Pixel size	YES	m	float	
Aspect ratio of pixels	YES		float	height of the pixel / width of the pixel
Width of image	YES	pixel	integer	
Height of image	YES	pixel	integer	
Number of images	YES		integer	
Film speed	YES	Hz	float	frames per second
Lens focal length	YES		float	
Shutter time	YES	s	float	
Start time of movie	YES	s	float	time of the first image
End time of movie	NO	s	float	time of the last image
Time offset	NO	s	float	delay between transducer T ₀ -signal and exposure start of movie T ₀ -image
Data source	NO		coded	see 2.4
Description	NO		string	
Camera id	NO		string	
Camera type	NO		string	
Lens id	NO		string	
Lens type	NO		string	
Focus	NO		string	
Aperture	NO		string	
Format of movie file	NO		string	e.g. AVI
Colour	NO		string	e.g. B/W, RGB, YUV
Compression code	NO		string	e.g. Indeo
Compression quality	NO		string	e.g. 85%
Keyframes	NO		integer	
Time vector filename	NO		filereference	one component data file in the Channel-subdirectory
Image history filename	NO		filereference	
Correction parameter file	NO		filereference	
Movie images corrected	NO		coded	see 2.8
Comments	NO		string	
#End of movie				

1.3.6.2 Correction parameter file

The correction parameter file is optional. It is referenced as value of "Correction parameter file" in the *moving image information file*. The file content for the correction method "bundle adjustment" has to be:

File name:	"filename".cor, where "filename" is identical to the <testnumber>_<movie id>.
-------------------	--

Location:	Movie-subdirectory			
Contents (for example see 4.1.5.2)				
Field descriptor	Mand.	Unit	Data type	Remark
Distortion correction type	YES		coded	bundle adjustment
Pixel distance x	YES	m	float	
Pixel distance y	YES	m	float	
Principal point x	YES	pixel	float	deviation from the center of the image (positive from left to right)
Principal point y	YES	pixel	float	deviation from the center of the image (positive from left to right)
Calibrated focal length	YES	m	float	as positive value
Distortion unit	YES		coded	pixel or mm, for the correction coefficients
Distortion correction A1	YES		float	1. corr. coeff. for radial symmetrical distortion
Distortion correction A2	YES		float	2. corr. coeff. for radial symmetrical distortion
Distortion correction A3	YES		float	3. corr. coeff. for radial symmetrical distortion
Distortion correction B1	YES		float	1. corr. coeff. for radial asymmetrical distortion
Distortion correction B2	YES		float	2. corr. coeff. for radial asymmetrical distortion
Distortion correction C1	YES		float	affinity
Distortion correction C2	YES		float	non-orthogonality
Distortion correction R0	YES		float	2. zero crossing of the distortion curve

1.3.6.3 Image history file

The image history file is optional. It is referenced as value of *Image history filename* in the moving image information file. The descriptors are not mandatory. They are unique but their position order shall show the time history of the single processing steps. The numbering of the descriptors is used to differentiate between twice or more usage of the same processing item.

File name:	"filename".imh, where "filename" is identical to the <testnumber>_< movie id >.		
Location:	Movie-subdirectory		
Contents			
Field descriptor	Mandatory	Data type	Remark
Image processing system	NO	string	with version number
Image interpolation	NO	string	with version number
Sharpening i	NO	string	typically 1 integer value
Colour matrix i	NO	string	
White balance i	NO	string	typically 3 integer values
Brightness i	NO	string	single or matrix of integer
Contrast i	NO	string	single or matrix of integer
Saturation i	NO	string	integer or float
Hue i	NO	string	typically integer
Gamma i	NO	string	typically 1 float value

1.3.7 Photo information

The descriptive information about all fotos has to be stored within one photo information file in the Photo-subdirectory.

File name:	"filename".mmi, where "filename" is identical to <testnumber>_Photo.			
Location:	Photo-subdirectory			
Contents (for example see 4.1.6)				
Field descriptor	Mand.	Unit	Data type	Remark
Number of photos	YES		integer	NOVALUE is not allowed
... descriptors, which are valid for all photos				
For each photo, if 'Number of photos' > 0				
#Begin of photo				
Photo id	YES		string	Id of the photo for referencing
Testobject	YES		reference	type of testobject in test information file
Classification	YES		coded	see 2.7
Width of image	YES	pixel	integer	
Height of image	YES	pixel	integer	
Aspect ratio of pixels	YES		float	Height of the pixel / width of the pixel
Name of photo file	YES		filereference	
Photographer	NO		string	
Description	NO		string	
Camera type	NO		string	
Direction	NO		string	e.g. left hand side
Aperture	NO		string	
Exposure time	NO	s	float	
Format of photo file	NO		string	e.g. TIFF or JPEG file format
Colour	NO		string	e.g. B/W, RGB, YUV
Compression	NO		string	
Comments	NO		string	
#End of photo				

1.3.8 Additional information files

The descriptive information about media objects like documents or reports has to be stored within one information file in the corresponding subdirectory. These information files are optional.

File name:	"filename".mmi, where "filename" is identical to the <testnumber>_<mediatype>.		
Location:	corresponding subdirectory e.g. Report		
Contents (for example see 4.1.7)			
Field descriptor	Mandatory	Data type	Remark
Number of <media objects>	YES	integer	NOVALUE is not allowed
... descriptors, which are valid for all <mediatypes>			

For each <mediatype>, if 'Number of <mediatypes >' > 0			
#Begin of <mediatype>			
Filename	YES	filereference	
Description	NO	string	
Format of file	NO	string	e.g. PDF
Originator	NO	string	
#End of <mediatype>			

1.4 Data files

1.4.1 General rules

The following rules specify the general handling of data files (see main document 5.2).

The data block of each data file starts with the separator line '#Start of data' and may be consisting of one or more columns. The columns are separated by one or multiple tabulation stops.

Some common used data structures are predefined in the following chapters. The column description of the predefined data structures may be omitted. **MultiChannel** has to be used for all data structures which are not predefined or agreed between the exchanging partners. In this case all columns have to be described in the header section. All descriptors which are identical for all columns shall be positioned before the column block structure.

1.4.2 Channel data files

Channel data have to be stored within one component data files in the Channel-subdirectory.

Allowed filenames are built by the <testnumber>, the <channelcode> defined in the related electronic document *Channel Codes* and the <codeextension>.

File name:	"filename".mmd, where "filename" is identical to <testnumber>_<channelcode>_<codeextension>.mmd			
Location:	Channel-subdirectory			
Contents (for example see 4.2.3)				
Field descriptor	Mand.	Unit	Data type	Remark
Data structure	YES		coded	Channel (see 2.2)
Instrumentation standard	YES		string	
Name of the channel	YES		string	
Data source	YES		coded	see 2.4
Data status	YES		coded	see 2.5
Unit	YES		coded	see 2.17 and "Dimension" in related electronic document <i>Channel Codes</i>
Cut off frequency	YES	[Hz]	float	-3dB frequency of Pre-filter
Channel amplitude class	YES		float	see ISO 6487
Sampling interval	YES	[s]	float	time step
Bit resolution	YES		integer	
Time of first sample	YES	[s]	float	'minus' before impact
Number of samples	YES		integer	

Reference channel	YES		coded	see 2.6
Reference channel name	NO		reference	<channelcode> of the time reference channel if 'Reference channel' is explicit
Laboratory channel code	NO		string	
Customer channel code	NO		string	
Channel code	NO		coded	see "Channel code" in related electronic document <i>Channel Codes</i> .
Channel frequency class	NO		coded	see "Filter class" in related electronic document <i>Channel Codes</i> .
Transducer type	NO		string	
Transducer id	NO		string	
Uuid	NO		string	universally unique identifier
Prefilter type	NO		string	anti-aliasing filter
First global maximum value	NO		float	same unit as used in the data section
Time of maximum value	NO	[s]	float	
First global minimum value	NO		float	same unit as used in the data section
Time of minimum value	NO	[s]	float	
Start offset interval	NO	[s]	float	'minus' before impact
End offset interval	NO	[s]	float	'minus' before impact
Offset post test	NO		float	same unit as used in the data section
Inverse sensitivity	NO		float	[unit / sensor output]
Inverse polynom coeff A	NO		float	[unit / (sensor output)^3]
Inverse polynom coeff B	NO		float	[unit / (sensor output)^2]
Inverse polynom coeff C	NO		float	[unit / (sensor output)^1]
Inverse polynom coeff M	NO		float	same unit as used in the data section
Offset pre test	NO		float	[sensor output]
Loadcell width	NO	m	float	mandatory for loadcell channels width of loadcell
Loadcell height	NO	m	float	mandatory for loadcell channels height of loadcell
Loadcell top left Y	NO	m	float	mandatory for loadcell channels defines top, left of loadcell with reference to the loadcell matrix origin
Loadcell top left Z	NO	m	float	mandatory for loadcell channels defines top, left of loadcell with reference to the loadcell matrix origin
Transducer natural frequency	NO	[Hz]	float	
Transducer damping ratio	NO	[1]	float	
Calibration date	NO		date	
Calibration due date	NO		date	
Comments	NO		string	
#Start of data				
... Data section ...				

1.4.3 Multi column data files

Data which is not specified within this document have to be stored within multicolumn data files in the media specific-subdirectory.

File name:	"filename".mmd		
Location:	media specific subdirectory		
Contents (for example see 4.2.1)			
Field descriptor	Mandatory	Data type	Remark
Data structure	YES	coded	MultiChannel (see 2.2)
Description	NO	string	
... all descriptors defined in 1.3 and 1.4, if they are valid for all columns			
#Start of data			
... Data section ...			
Contents if 'Data structure' is MultiChannel			
Number of columns	YES	integer	NOVALUE is not allowed
#Begin of column			
Name	YES	string	title of the column
Unit	YES	string	see 2.17
Format	YES	coded	see 2.14
... all descriptors defined in the chapters 1.3 and 1.4, if they are valid for the specific column			
Comments	NO	string	
#End of column			

1.4.4 Static measurement data file

Static measurement data may consist of points, lines and areas and is stored as a multicolumn data file in the Static subdirectory.

File name:	"filename".mmd, where "filename" is identical to <testnumber>_ StaticData.		
Location:	Static-subdirectory		
Contents (for example see 4.2.4)			
Field descriptor	Mandatory	Data type	Remark
Data structure	YES	coded	StaticData (see 2.2)
#Start of data			
... Data section ...			
Column specification if 'Data structure' is StaticData			
Field descriptor	Value	Remark	
Number of columns	7		
Description of column 1			
Name	Name		
Unit	1		

Format	string	shall be the <channelcode>
Description of column 2		
Name	Refsys	
Unit	1	
Format	reference	Reference system id (see 1.3.4 and 2.3)
Description of column 3		
Name	Index	
Unit	1	
Format	string	Index of line element, NOVALUE for points
Description of column 4		
Name	Classification	Classification, see 2.7
Unit	1	
Format	coded	see 2.7
Description of column 5		
Name	X	
Unit	m	
Format	float	
Description of column 6		
Name	Y	
Unit	m	
Format	float	
Description of column 7		
Name	Z	
Unit	m	
Format	float	

1.4.5 Reference system data file, Camera position file and Object data file

The relations between all reference systems described in the reference system information file have to be stored within one reference system data file.

The position and orientation of all cameras should be stored within one camera position file.

All media objects which can be described by a position and orientation should be stored in an object data file.

All these files are multicolumn data files with the data structure 6DoF in the Object-subdirectory.

File name:	"filename".mmd, where "filename" is identical to the <testnumber>_Reference or <testnumber>_CameraPosition or <testnumber>_Object		
Location:	Object-subdirectory		
Contents (for example see 4.2.2)			
Field descriptor	Mandatory	Data type	Remark
Data structure	YES	coded	6DoF (see 2.2)
#Start of data			
... Data section ...			
Column specification if 'Data structure' is 6DoF			

Field descriptor	Value	Remark
Number of columns	10	
Description of column 1		
Name	Name	
Unit	1	
Format	reference	Reference system id (see 1.3.4 and 2.3) , object id or Movie id from moving image information file
Description of column 2		
Name	RefSys	
Unit	1	
Format	reference	Reference system id (see 1.3.4 and 2.3)
Description of column 3		
Name	Time	
Unit	s	
Format	float	
Description of column 4		
Name	X	
Unit	m	
Format	float	
Description of column 5		
Name	Y	
Unit	m	
Format	float	
Description of column 6		
Name	Z	
Unit	m	
Format	float	
Description of column 7		
Name	QuaternionW	
Unit	1	
Format	float	
Description of column 8		
Name	QuaternionX	
Unit	1	
Format	float	
Description of column 9		
Name	QuaternionY	
Unit	1	
Format	float	
Description of column 10		
Name	QuaternionZ	
Unit	1	
Format	float	

1.4.6 3D point data file

The coordinates of a three dimensional point can be combined and stored in a multicolumn data file of data structure **Point** in the Channel-subdirectory. The filename includes the Channel code with the direction “M”. The columns contain the values for the Time, X, Y and Z component. The data structure **PointStdDev** is an enlargement with 3 additional columns for the standard deviations of the spatial components.

File name:	“filename”.mmd, where “filename” is identical to <testnumber>_<channelcode>_<codeextension>.mmd with the direction “M” in the Channel code		
Location:	Channel-subdirectory		
Contents (for example see 4.2.5)			
Field descriptor	Mandatory	Data type	Remark
Data structure	YES	coded	Point, PointStdDev (see 2.2)
#Start of data			
... Data section ...			
Column specification if ‘Data structure’ is Point			
Field descriptor	Value	Remark	
Number of columns	4		
Description of column 1			
Name	Time		
Format	float		
Unit	s		
Description of column 2			
Name	X		
Format	float		
Unit	m		
Description of column 3			
Name	Y		
Unit	m		
Format	float		
Description of column 4			
Name	Z		
Unit	m		
Format	float		
Column specification if ‘Data structure’ is PointStdDev			
Number of columns	7		
Field descriptor	Value	Remark	
... the 4 column descriptions of Points and in addition			
Description of column 5			
Name	SX		
Format	float		

Unit	m	
Description of column 6		
Name	SY	
Unit	m	
Format	float	
Description of column 7		
Name	SZ	
Unit	m	
Format	float	

1.5 Comment files

All comment files contain unformatted text. To reference a data channel use the channel code with an appended colon (for example see 4.3.2).

2 Coded values

2.1 Valid values for the descriptor ‘Data format edition number’

Value	Remark
2.0	current version
2.0draft	for testing only; current draft version

2.2 Valid values for the descriptor ‘Data structure’

Value	Remark
MultiChannel	user specific number of columns; see 1.4.2
Channel	1 column; see 1.4.2
StaticData	7 columns; see 1.4.4
Point	4 columns; see 1.4.6
PointStdDev	7 columns; see 1.4.6
6DoF	10 columns; see 1.4.5

2.3 Valid values for the descriptor ‘Reference system id’

Value	Remark
LOC	local coordinate system for transducers according to SAE J211
nST	testobject <i>n</i> static (see related electronic document <i>Channel Codes</i>)
nT0	testobject <i>n</i> at T0 (see related electronic document <i>Channel Codes</i>)
nDY	testobject <i>n</i> dynamic (see related electronic document <i>Channel Codes</i>)
i	3 digit number <i>i</i> with leading zeros (000 = undefined)

2.4 Valid values for the descriptor ‘Data source’

Value	Remark
transducer	channel data has been generated by transducer
camera	channel data has been generated by camera
simulation	channel data has been generated by simulation
calculation	channel data has been calculated from other channels
parameter	channel data can be constant or limit curve
NOVALUE	undefined / other

2.5 Valid values for the descriptor 'Data status'

Value	Remark
ok	
channel failed	
meaningless data	
no data	
questionable data	
scaling factor applied	
system failed	
linearised data	
NOVALUE	

2.6 Valid values for the descriptor 'Reference channel'

Value	Remark
implicit	Time reference is given with the descriptor values 'Time of first sample' and 'Sampling interval'.
explicit	Explicit time channel exists in test data. Channel name is given with the descriptor 'Reference channel name'.
NOVALUE	No time reference is available. For example in case of constant channels (filter class 'X').

2.7 Valid values for the descriptor 'Classification'

Value	Remark
PRE	before the test procedure
DURING	during the test procedure
POST	after the test procedure
CONSTANT	fixed relation for the whole time
SENSOR	Related to the preparation of the test (image of the transducer)
NOVALUE	no classification is available

2.8 Valid values for the descriptor 'Movie images corrected'

Value	Remark
YES	The images of the movie are corrected.
NO	The images of the movie are not corrected.

2.9 Valid values for the descriptor 'Distortion correction type'

The descriptor 'Distortion correction type' is used within correction parameter files to distinguish the type of correction.

Value	Remark
bundle adjustment	see 1.3.6.2

2.10 Valid values for the descriptor ‘Distortion unit’

Value	Remark
mm	see 1.3.6.2
pixel	see 1.3.6.2

2.11 Valid values for the descriptor ‘Gender’

Value	Remark
male	see 1.3.3.4
female	see 1.3.3.4

2.12 Valid values for the descriptor ‘Time zone’

Value	Remark
GMT	Greenwich Mean Time
GMT+i	Greenwich Mean Time + i hours (0<i<13)
GMT-i	Greenwich Mean Time - i hours (0<i<12)

2.13 Valid values for block descriptors

Blockbegin- and blockend-descriptors are used within information and data files to structure the information lines. Blocks are surrounded by a ‘#Begin of <value>’ and a ‘#End of <value>’ descriptor. Predefined values are listed in the following table.

Value	Remark
column	used for the description section of multicolumn data files
testobject	used for testobject information in the mme file
NHTSA	used for additional NHTSA specific information
biomechanical	used for the additional information of biomechanical test environments
reference	used within reference system information and data files
movie	used for movie information files
photo	used for photo information files
channel	used for channel information files

2.14 Valid values for the format specification

Value	Remark
integer	see 1.2

float	see 1.2
string	see 1.2
date	see 1.2
datetime	see 1.2
coded	see 1.2
reference	see 1.2
filereference	see 1.2

2.15 Valid values for the data origin

Value	Remark
T	origin of the channel data is a transducer
F	origin of the channel data is filmanalysis
S	origin of the channel data is simulation
C	the channel data is a combination of different origin
0	undefined / other

2.16 Valid values for the codeextension

The <codeextension> is a concatenation of the 'Reference system id' in table 2.3 and the 'Data origin' in table 2.15. Predefined values for the <codeextension> are all possible combinations of the values listed in tables 2.3 and 2.15. Examples are shown in the following table.

Value	Remark
1T0S	simulation data in the coordinate system of testobject 1 at stage T0
1T0F	filmanalysis data in the coordinate system of testobject 1 at stage T0
1DYF	filmanalysis data in the coordinate system of the moving testobject 1
DSTC	calculated data of a dummy part (e.g. headimpactor) in a static coordinate system (e.g. photogrammetric measurement)
TSTF	filmanalysis data in the static testrig coordinate system
001F	filmanalysis data in the coordinate system 001 specified in the reference system information file
002S	simulation data in the coordinate system 002 specified in the reference system information file
LOCT	transducer data in the local coordinate system

2.17 Allowed units

The SI units are currently divided into base units and derived units, which together form what is called "the coherent system of SI units." The units allowed to use for the data exchange are described in their notation in the following table. Additional units may be used if agreed between the exchanging partners. For the descriptor 'Unit' the spelling described in the column 'Value' has to be used.

For all other descriptors, where the value deviates from the default, the unit enclosed in squared brackets has to follow the numerical value. One or multiple blanks (ASCII 32) are allowed for the interspace.

Unit	Quantity	Remark
m	Length	base unit
s	Time	base unit
kg	Mass	base unit
A	Electric Current	base unit
K	Temperature	base unit
cd	Luminous Intensity	base unit
rad	Angle	coherent derived unit
sr	Solid Angle	coherent derived unit
Hz	Frequency	coherent derived unit
N	Force	coherent derived unit
Pa	Pressure	coherent derived unit
J	Energy	coherent derived unit
W	Power	coherent derived unit
C	Electric Charge	coherent derived unit
V	Voltage	coherent derived unit
lm	Luminous Flux	coherent derived unit
lx	Illuminance	coherent derived unit
m/s	Velocity	derived unit
m/(s*s)	Acceleration	derived unit
rad/s	Angle Velocity	derived unit
rad/(s*s)	Angle Acceleration	derived unit
Nm	Moment	derived unit
kg*m/s	Impulse	derived unit
V/A	Resistance	derived unit
m*m	Area	derived unit
m*m*m	Volume	derived unit
Cd/(m*m)	Luminance	derived unit
1	Unit One	without unit or ratio of two mutually comparable quantities
%	Percent	symbol for the number 0.01
The following units have to be enclosed in squared brackets if used as descriptor values		
mm	Length	decimal submultiple of the base unit
µm	Length	decimal submultiple of the base unit
ms	Time	decimal submultiple of the base unit
µs	Time	decimal submultiple of the base unit
pixel	Image Unit	accepted Non-SI unit
L	Volume	accepted Non-SI unit
°	Angle	accepted Non-SI unit
°/s	Angle Velocity	accepted Non-SI unit
°/(s*s)	Angle Acceleration	accepted Non-SI unit
dB	Decibel	accepted Non-SI unit
°C	Temperature	accepted Non-SI unit

2.18 Valid values for the descriptor 'Type of the test'

The values for 'Type of the test' can be expanded by the exchanging partners.

Value	Remark
Airbag Test	
Bumper Test	
Car To Car Impact	
Component Test	Test of vehicle components
Door Intrusion	
Drop Test	
Frontal Impact	
Frontal Sled Test	Simulation of a frontal impact
Misuse Test	
Other	None of the listed types of test
Pedestrian Protection	
Pendulum Test	
Pressure Test	
Rear Impact	
Rear Sled Test	Simulation of a rear impact
Rollover Leftside	
Rollover Rightside	
Roof Crush	
Side Impact Leftside	
Side Impact Rightside	
Sled Test Leftside	Simulation of a side impact from the left side
Sled Test Rightside	Simulation of a side impact from the right side
Towing Test	

2.19 Valid values for the descriptor 'Regulation'

The regulation can be a reference to a national standard or to a consumer organization. National standards are normally followed by a space ASCII(32) and a number resp. two numbers separated by '/' ASCII(47).

Value	Remark
ADR	National Standard of Australia
AIS	National Standard of India
CMVSS	National Standard of Canada
CONTRAN	National Standard of Brazil
ECE-R	Standard of the UN
EG	Standard of European Union
FMVSS	National Standard of US
GB	National Standards of the People's Republic of China
GTR	Worldwide Standard of the UN
KMVSS	National Standard of South Korea

TRIAS	National Standard of Japan
ANCAP	Australian New Car Assessment Program
CNCAP	China New Car Assessment Program
EuroNCAP	European New Car Assessment Program
IIHS	Insurance Institute For Highway Safety
JNCAP	Japan New Car Assessment Program
KNCAP	Korean New Car Assessment Program
LatinNCAP	Latin New Car Assessment Program
SINCAP	US Side Impact New Car Assessment Program
USNCAP	US New Car Assessment Program
Combined	A combination of multiple regulations
Internal	Company specific regulation
Other	None of the listed standards or consumer tests

3 Hints

For future use.

4 Examples

4.1 Examples of information files

4.1.1 Examples of test information files

4.1.1.1 Example of MME file

Filename: 2011ISO2.mme

see 1.3.2

```

Data format edition number      :2.0
Timestamp                       :2009-07-07 09:25:15
Time zone                       GMT+1
Laboratory name                 :ALPHA Car Test Laboratory
Laboratory contact name        :Frank N. Stein
Laboratory contact phone       :+49-222/123-4567
Laboratory contact fax         :+49-222/123-8901
Laboratory contact email       :frank.stein@alpha.cartest.com
Laboratory test ref number     :2001WG3
Customer name                   :ISO/TC22/SC12/WG3 Safety Laboratory
Customer test ref number       :2001ISO1
Customer project ref number    :ISOTC22
Customer order number          :SC12WG3
Customer cost unit              :2001/0
Customer contact name          :Mary Land
Customer contact phone         :+44-123/555-123
Customer contact fax           :+44-123/555-456
Customer contact email         :mary.land@iso.tc22.sc12.wg3.uk
Title                           :Simulation Test
Type of the test                Car To Car Impact
Subtype of the test             :40% Offset both
Regulation                      Internal
Date of the test                :2009-03-03
Reference temperature           22.5 [°C]
Relative air humidity           :75
Number of test objects         :2
#Begin of testobject
Type                            1
Filename                        2011ISO2_1.INF
#End of testobject
#Begin of testobject
Type                            B
Filename                        2011ISO2_B.INF
#End of testobject

```

4.1.1.2 Example of additional NHTSA test information

Filename: 2009NHTSA2.mme

see 1.3.2.1

```

Data format edition number      :2.0
...
#Begin of NHTSA
Test type                       NCA
Test configuration              VTB
Track surface                   CON
Track condition                 DRY
...
#End of NHTSA

```

4.1.1.3 Example of additional biomechanical test information

Filename: 2011BIOMECH2.mme **see 1.3.2.2**

```
Data format edition number :2.0
...
#Begin of biomechanical
Financial support          EC
Project ref number       EC09-12345
Project contact name     Beerlustconi
Project contact email    beerlustconi@projects.eu
#End of biomechanical
```

4.1.2 Examples of object information files

4.1.2.1 Example of vehicle information file

Filename: 2011ISO2_1.mmi **see 1.3.3.1 and 1.3.3.2**

```
Name          Vehicle A
Velocity      15.72
Mass          1430.00
Impact side   2
Driver position 1
Class         Small Family Car
Code          A0
Ref number    007-008
Offset        40
#Begin of NHTSA
Vehicle make  CarManu
Vehicle model Eagle
Vehicle year  2009
...
#End of NHTSA
```

4.1.2.2 Example of barrier information file

Filename: 2011ISO2_B.mmi **see 1.3.3.1 and 1.3.3.2**

```
Name          Fixed barrier
Velocity      0.00
Mass          1500.00
Impact side   NOVALUE
Class         NOVALUE
Code          xyz
Ref number    1111-012
Barrier width  3.2
Barrier height 1.64
Reference system id BST
Comments      according to the SAE J211 reference coordinate system
Origin X      0.12
Origin Y      -1.4
Origin Z      -1.8
Number of loadcells 64
#Begin of NHTSA
Barrier shape LCB
Rigid or deformable barrier R
Angle of fixed barrier 0
```

Diameter of pole barrier NOVALUE
 NHTSA Comments NO DATA COLLECTED ON A1, B1, C1, D1, D2, D3,
 NHTSA Comments D4,D5,D6,D7,D8,D9
 #End of NHTSA

4.1.2.3 Example of occupant information file

Filename: 2011ISO2_11.mmi **see 1.3.3.4**

Gender male
 Age NOVALUE
 Comments V3239.OCC
 Comments
 Comments - DRIVER OCCUPANT INFORMATION
 Dummy Type H3
 Dummy subtype Build Level D
 Dummy Manufacturer Ser No VECTOR, S/N:034
 Dummy Modifications UNMODIFIED
 Dummy temperature NOVALUE
 Out of position NO
 Head to Windshield Header .350
 Head to Windshield .635
 Head to Side Header .245
 Head to Side Window .325
 Chest to Dash .515
 Chest to Steering Wheel .320
 Arm to Door .126
 Hip to Door .154
 Knees to Dash .220
 Head to Seatback NOVALUE
 Neck to Seatback NOVALUE
 Chest to Seatback NOVALUE
 Knee to Seatback NOVALUE
 Seat Track Position RW
 1st Contact for Head AB
 2nd Contact for Head NO
 1st Contact for Chest Abdo AB
 2nd Contact for Chest Abdo NO
 1st Contact for Legs DP
 2nd Contact for Legs SC
 Head Injury Criterion HIC 377
 Lo HIC Time Interval .0528
 Up HIC Time Interval .0887
 Thorax Peak Accel (CLIP3M) 426.59
 L Femur Peak Load 3534
 R Femur Peak Load 4642
 Chest Severity Index NOVALUE
 Lap Belt Peak Load 6474
 Shoulder Belt Peak Load 5109
 Thoracic Trauma Index NOVALUE
 Pelvic Acceleration NOVALUE

4.1.2.4 Example of restraint system information file

Filename: 2011ISO2_11SEBE.mmi **see 1.3.3.5**

Restraint type 3PT
 Restraint mount BC
 Restraint Deployed NA

4.1.3 Example of reference system information file

Filename:	2011ISO2_Reference.mmi	see 1.3.4
Number of references	5	
#Begin of reference		
Reference system id	LOC	
Description	local transducer systems according to SAE J211	
X origin	center of gravity of the transducer	
Y origin	center of gravity of the transducer	
Z origin	center of gravity of the transducer	
X direction	x-direction of the transducer	
Y direction	y-direction of the transducer	
Z direction	z-direction of the transducer	
#End of reference		
#Begin of reference		
Reference system id	1T0	
Description	vehicle system at time 0	
X origin	center of the front axle	
Y origin	center of the front axle	
Z origin	center of the front axle	
X direction	from the front of the vehicle to the rear	
Y direction	from the left to the right of the vehicle	
Z direction	opposite to the force of gravity	
#End of reference		
#Begin of reference		
Reference system id	1DY	
Description	vehicle system dynamic	
X origin	center of the front axle	
Y origin	center of the front axle	
Z origin	center of the front axle	
X direction	from the front of the vehicle to the rear	
Y direction	from the left to the right of the vehicle	
Z direction	opposite to the force of gravity	
#End of reference		
#Begin of reference		
Reference system id	001	
Description	vehicle system at T0 / direction of the axes according to SAE J211	
X origin	center of the front axle	
Y origin	center of the front axle	
Z origin	center of the front axle	
X direction	from the rear of the vehicle to the front	
Y direction	from the left to the right of the vehicle	
Z direction	in the direction of the force of gravity	
#End of reference		
#Begin of reference		
Reference system id	TST	
Description	test rig static	
X origin	marker on the floor in front of the barrier	
Y origin	marker on the floor in front of the barrier	
Z origin	marker on the floor in front of the barrier	
X direction	from the barrier to the vehicle, opposite to the driving direction	
Y direction	from the left to the right of the vehicle	
Z direction	opposite to the force of gravity	
#End of reference		

4.1.4 Example of channel information file

Filename:	2011ISO2_Channel.mmi	see 1.3.5
Number of channels	75	

```

#Begin of channel
Channel code          11HEAD0000H3ACXA
#End of channel
#Begin of channel
Channel code          11HEAD0000H3ACYA
#End of channel
#Begin of channel
...

```

4.1.5 Examples of moving image information

4.1.5.1 Example of moving image information file

```

Filename:    2011ISO2_Movie.mmi                see 1.3.6.1
Number of movies          7
Comments
Comments                  information valid for all movies
Comments
Pixel size      12 [µm]
Aspect ratio of pixels    :1.00
Origin                    :Crashtest
Camera type                :KAPPA ROC
Format of movie file      :AVI
Colour                     :RGB
Movie images corrected    :NO
Comments
Comments                  specific information of movie 1
#Begin of movie
Movie id        L1
Name of movie file        :LEFTATOT.AVI
Camera id       KAPPA12
Width of image            :512
Height of image           :384
Number of images          :351
Film speed                :1000
Start time of the movie -0.05
Time offset     360 [µs]
End time of the movie 0.3
Description                :total view of vehicle A from the left side
Lens id         14579435
Lens type                  :Schneider
Lens focal length         :10 [mm]
Focus                      :infinite
Aperture                   :5.6 - 8
Shutter time               :250 [µs]
Compression code      :X264
Compression quality   :23
Keyframes                  :7
Time vector filename       :2011ISO2_10VEHC000000TI00_TSTF.mmd
Image history filename     :2011ISO2_L1.imh
Correction parameter file  :2011ISO2_L1.cor
#End of movie
Comments
Comments                  specific information of movie 2
#Begin of movie
Movie id        R1
Description                :total view of vehicle A from the right side
Camera id       KAPPA67
...

```

4.1.5.2 Example of COR file

Filename: 2011ISO2_R1.cor

see 1.3.6.2

```

Distortion correction type :bundle adjustment
Pixel distance x          :16 [µm]
Pixel distance y          :16 [µm]
Principal point x         :-9.38
Principal point y         :-8.25
Calibrated focal length   :10.128 [mm]
Distortion unit           :mm
Distortion correction A1  :-1.1685e-003
Distortion correction A2  :5.3873e-006
Distortion correction A3  :2.8685e-007
Distortion correction B1  :-1.4558e-005
Distortion correction B2  :-3.2337e-005
Distortion correction C1  :6.6139e-007
Distortion correction C2  :3.6798e-005
Distortion correction R0  :3.413

```

4.1.6 Example of photo information file

Filename: 2011ISO2_Photo.mmi

see 1.3.7

```

Number of photos          :6
Comments                  :
Comments                  : information valid for all photos
Comments                  :
Width of image            :1170
Height of image           :1000
Aspect ratio of pixels    :1.00
Photographer              Hamilton
Camera type               :ETA 007
Aperture                  4 – 5.6
Exposure time             :0.008
Format of photo file      :TIFF
Colour                    :RGB
Compression               :LZW
Comments                  :#####
Comments                  : specific information of photo 1
#Begin of photo
Photo id                  1
Testobject                1
Classification            POST
Name of photo file        :BRIGPOST.TIF
Description                :partial view of the front of vehicle B
Direction                 :right
#End of photo
Comments                  :#####
Comments                  : specific information of photo 2
#Begin of photo
Photo id                  2
Testobject                1
...

```

4.1.7 Example of report information file

Filename: 2011ISO2_Report.mmi

see 1.3.8

```

Number of reports        3
#Begin of report
Filename                 2011ISO2_Report.pdf

```

Description contains tables and diagrams
 #End of report
 ...

4.2 Examples of data files

4.2.1 Example of multi column data file

Filename: 2011ISO2_Steeringwheel_Movement.mmd see 1.4.2

```
Data structure MultiChannel
Number of columns 4
Comments Relative movement of the steering wheel hub
Comments
Description Time[s] X[m] Z[m] R[m]
#Begin of Column
Comments Timebase
Name Time
Unit s
Format float
#End of Column
#Begin of Column
Comments Movement in X-Direction relative to Time Zero
Name X
Unit m
Format float
#End of Column
#Begin of Column
Comments Movement in Z-Direction relative to Time Zero
Name Z
Unit m
Format float
#End of Column
#Begin of Column
Comments Resultant relative movement in XZ-plane
Name R
Unit m
Format float
#End of Column
#Start of data
-0.001 -6.60e-003 5.16e-003 8.38e-003
0.000 0.00e+000 0.00e+000 0.00e+000
0.001 1.20e-002 -1.95e-003 1.22e-002
0.002 4.02e-003 -8.98e-003 9.84e-003
0.003 5.04e-004 -1.56e-002 1.56e-002
0.004 -1.36e-004 -1.98e-002 1.98e-002
0.005 -3.13e-003 -1.37e-002 1.40e-002
0.006 -2.85e-003 -1.25e-004 2.86e-003
0.007 -3.75e-003 5.92e-003 7.01e-003
...
```

4.2.2 Example of reference system data file

Filename: 2011ISO2_Reference.mmd see 1.4.5

```
Data structure 6DoF
Comments Name Refsys Time X Y Z Qw Qx Qy Qz
#Start of data
1T0 TST CONSTANT 2.9522 -7.3176 1.6790 1.00000 0.00000 0.00000 0.00000
```

```

001 1T0 0.000 0.0000 0.0000 0.0000 0.00000 0.00000 1.00000 0.00000
1DY 1T0 -0.002 0.0340 -0.0001 0.0001 1.00000 0.00000 0.00000 0.00000
1DY 1T0 -0.001 0.0170 0.0002 -0.0001 1.00000 0.00000 0.00000 0.00000
1DY 1T0 0.000 0.0000 0.0000 0.0000 1.00000 0.00000 0.00000 0.00000
1DY 1T0 0.001 -0.0160 0.0005 0.0002 1.00000 0.00000 0.00000 0.00000
...

```

4.2.3 Examples of channel data

4.2.3.1 Example of channel data file with local transducer data

Filename: 2011ISO2_11HEAD0000H3ACXA_LOCT.mmd **see 1.4.2**

```

Data structure Channel
Instrumentation standard ISO 6487 (1987) / SAE J211 (MAR95)
Name of the channel :Head Acceleration X
Data source :transducer
Data status :ok
Unit :m/(s*s)
Cut off frequency :2000.0
Channel amplitude class :2000.0
Sampling interval :0.0001
Bit resolution :12
Time of first sample :0.0000
Number of samples :2500
Reference channel :implicit
Reference channel name :NOVALUE
Laboratory channel code :HEAD01AX
Customer channel code :1HEAD_X_ACC
Channel frequency class :1000
Transducer type :TAU 7270 A
Transducer id 071234
Transducer natural frequency 27000
Transducer damping ratio 0.3
Uuid NOVALUE
Calibration date NOVALUE
Calibration due date NOVALUE
Prefilter type :Butterworth, 6 pole
First global maximum value :+1.237802E+02
Time of maximum value :+0.18450
First global minimum value :-5.489905E+02
Time of minimum value :+0.06860
Start offset interval :-0.0500
End offset interval :+0.0000
Offset post test NOVALUE
Inverse sensitivity NOVALUE
Inverse polynom coeff A NOVALUE
Inverse polynom coeff B NOVALUE
Inverse polynom coeff C NOVALUE
Inverse polynom coeff M NOVALUE
Offset pre test NOVALUE
Loadcell width NOVALUE
Loadcell height NOVALUE
Loadcell top left Y NOVALUE
Loadcell top left Z NOVALUE
#Start of data
-4.788391E-01
...

```

4.2.3.2 Example of channel data file with filmanalysis data**Filename: 2011ISO2_11HEAD0000H3DSXV_1DYF.mmd** **see 1.4.2**

Data structure	Channel
Instrumentation standard	internal - dynamical vehicle system
Name of the channel	Head Displacement X
Data source	camera
Data status	ok
Unit	m
Cut off frequency	NOVALUE
Channel amplitude class	NOVALUE
Sampling interval	0.001
Bit resolution	NOVALUE
Time of first sample	-0.01
Number of samples	211
Reference channel	implicit
#Start of data	
0.468	
0.466	
...	

4.2.4 Example of static measurement data file**Filename: 2011ISO2_ StaticData.mmd** **see 1.4.4**

Data structure	StaticData						
Comments	Name	Refsys	Group	Classification	X	Y	Z
#Start of data							
11APILMI0000DSM0	1ST	NOVALUE	PRE	0.361	-0.7885	07172	
11APILMI0000DSM0	1ST	NOVALUE	POST	0.406	-0.7832	07255	
...							
10DASB	1ST	1	PRE	0.300	-0.450	0.655	
10DASB	1ST	2	PRE	0.301	-0.450	0.654	
10DASB	1ST	3	PRE	0.302	-0.450	0.653	
10DASB	1ST	4	PRE	0.303	-0.450	0.652	
...							

4.2.5 Example of 3D point data file**Filename: 2011ISO2_11HEADLEMI00DSMV_1T0F.mmd** **see 1.4.6**

Data structure	Point			
Comments	Time	X	Y	Z
#Start of data				
-0.0090	6.49e-001	-4.39e-001	7.30e-001	
-0.0080	6.31e-001	-4.36e-001	7.32e-001	
-0.0070	6.15e-001	-4.38e-001	7.31e-001	
-0.0060	5.98e-001	-4.40e-001	7.31e-001	
...				

4.2.6 Example of camera position file**Filename: 2011ISO2_CameraPosition.mmd** **see 1.4.5**

Data structure	6DoF									
Comments	Movielid	Refsys	Time[s]	X[m]	Y[m]	Z[m]	Qw	Qx	Qy	Qz
#Start of data										
L1	TST	0.000	2.9521	-7.3178	1.6081	0.76506	0.64370	0.01340	0.01277	

ISO/TS 13499 – RED A : 2011(E)

L1	TST	0.001	2.9522	-7.3177	1.6080	0.76506	0.64370	0.01341	0.01277
...									
L1	TST	0.150	2.9525	-7.3177	1.6081	0.76506	0.64370	0.01347	0.01272
IN1	1T0	CONSTANT	0.8000	-0.4000	0.0200	0.96593	0.00000	-0.25882	0.00000
IN2	1T0	CONSTANT	0.8000	-0.4000	0.0280	0.96126	0.00000	-0.27564	0.00000
...									

4.3 Example of comment files

4.3.1 Example of test comment file

Filename: **2011ISO2.txt**

see 1.5

The car to car test was performed on 3rd of March 2011 at ALPHA Car Test Laboratory. The airbags of vehicle A had to be exchanged before the test.

4.3.2 Example of channel comment file

Filename: **2011ISO2_Channel.txt**

see 1.5

Following problems occurred:

13HEAD0000H3ACXA: large deviations at post test calibration...